

DR 130

Standard Equipment

Carrier (options)

Trailer (standard)
Skid
Truck
Track

Mast

8" x 12" Tubing
Hydraulic Cylinders raise mast into drilling position
Working Height: 19 ft. (drilling position)
27 ft. (w/ mast ext.)

Hydraulic Systems

System One Hydraulic Pressure: 3000 PSI
Hydraulic Pump - Hydrostatic
System Two Pump - Pressure Compensated
Piston: 2500 PSI
Separate Circuits for Rotation and Feed

Engine

239 cu.in. 4 cyl. 80 HP water-cooled diesel
239 cu.in. 4 cyl. 115 HP Turbo-charged water-cooled diesel
Truck PTO

Tophead Drive

Tophead Rotation and Torque 0-150 RPM:
2525 ft.lbs. (all speeds)
Drill Head travel speed: 1.2 ft/sec.
Top Feed Swivel with 2" water course

Pulldown / Pullback

Tophead Travel - 11'4"
Pulldown - 5,400 lbs.
Pullback - 10,600 lbs.

DeepRock

2129 South V W Goodwin BLVD
Marquez, Texas 77865

Phone: (855) 457-4469 (Toll-Free)

Email: sales@deeprock.com

www.deeprock.com

Trailer (standard)

Construction - MIG Welded Heavy Duty Rectangular Tubing
Ball Hitch - 2 5/16" Hitch w/ Actuated Hydraulic Brake
3" Pintel (optional)
Electric Brake (optional)

Dimensions (trailer-mounted)

Length - 22'
Width - 8'
Height - 8' (travel)
Weight - 8500+ lbs. (depending on options)

Options

Hydraulic Leveling Jacks
Hydraulic Break-Out for Drill Rod
Hydraulic Mast Extension w/ Winch
Hydraulic 2"x3"x13" Centrifugal Pump
Hydraulic 3"x4"x13" Centrifugal Pump
Gardner Denver 4.5"x5" (truck mount only)
Gardner Denver 5"x6" (truck mount only)
Drill Stem Rack
Night Drilling Illumination

For further information please refer to attached literature