

DR 130

Standard Equipment

Carrier (options)

Trailer (standard)
Skid
Truck
Track

Mast

8" x 12" Tubing
Hydraulic Cylinders raise mast into drilling position
Working Height: 19 ft. (drilling position)
27 ft. (w/ mast ext.)

Hydraulic Systems

System One Hydraulic Pressure: 3000 PSI
Hydraulic Pump - Hydrostatic
System Two Pump - Pressure Compensated
Piston: 2500 PSI
Separate Circuits for Rotation and Feed

Engine

239 cu.in. 4 cyl. 80 HP water-cooled diesel
239 cu.in. 4 cyl. 115 HP Turbo-charged
water-cooled diesel
Truck PTO

Tophead Drive

Tophead Rotation and Torque 0-150 RPM:
2525 ft.lbs. (all speeds)
Drill Head travel speed: 1.2 ft/sec.
Top Feed Swivel with 2" water course

Pulldown / Pullback

Tophead Travel - 11'4"
Pulldown - 5,400 lbs.
Pullback - 10,600 lbs.

DeepRock

Manufacturing Company

2209 Anderson Road
PO Box 1
Opelika, AL 36803-0001

1-800-633-8798

phone: (334) 749-3377
fax: (334) 749-5601

www.deeprock.com

Trailer (standard)

Construction - MIG Welded Heavy
Duty Rectangular Tubing
Ball Hitch - 2 5/16" Hitch w/ Actuated
Hydraulic Brake
3" Pintel (optional)
Electric Brake (optional)

Dimensions (trailer-mounted)

Length - 22'
Width - 8'
Height - 8' (travel)
Weight - 8500+ lbs. (depending on options)

Options

Hydraulic Leveling Jacks
Hydraulic Break-Out for Drill Rod
Hydraulic Mast Extension w/ Winch
Hydraulic 2"x3"x13" Centrifugal Pump
Hydraulic 3"x4"x13" Centrifugal Pump
Gardner Denver 4.5"x5" (truck mount only)
Gardner Denver 5"x6" (truck mount only)
Drill Stem Rack
Night Drilling Illumination

**For further information please refer
to attached literature**